

**MT36-5VI****Reciprocating compressor, MT36JG5CVE**

Refrigerants: R22, Segment usage: Refrigeration MT, Compressor power supply

[V]: 220-240/1/50, Packing format: Single pack

PRODUCT DETAILS

Gross weight	27.88 Kilogram
Net weight	26.005 Kilogram
Volume	37.73 Liter
EAN	5702428662253
Approval	CCC CE UKCA
Auxiliary winding resistance (start winding) for single-phase compressors [Ohm]	4.23
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Capacity of capacitor A	25 µF
Capacity of capacitor B	135 µF
Capacity of capacitor C	10 µF
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	220-240/1/50
Configuration code	Single
Connection type	Rotolock
Cylinder	1
Description	MT036-5
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	1/2 in
Discharge connection size [in]	1 in
Drawing number	8501020e
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MT
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	50
Gauge port HP	None
Gauge port LP	Schrader

PRODUCT DETAILS

Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 °C
High Side TS Min	-35 °C
High Side Volume	0.3 L
High value of nominal voltage at 50Hz [V]	240 V
High value of voltage range at 50Hz [V]	264 V
In scope of WEEE and contain batteries	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	7.5 L
Low value of nominal voltage at 50Hz [V]	220 V
Low value of voltage range at 50Hz [V]	198 V
LRA	60 A
Main winding resistance for single-phase compressors [Ohm]	0.8
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	18.4 bar
MCC	22 A
Model number	MT36JG5CVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	220-240/1/50
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	160P
Packaging height [mm]	385 mm
Packaging length [mm]	330 mm
Packaging weight [Kg]	27 kg
Packaging width [mm]	295 mm
Packing format	Single pack
Packing quantity	1
Phase	1
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	Reciprocating compressor MT
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	2.5 kg
Refrigerants	R22
Rotational speed at 50Hz [rpm]	2900 rpm
SCIP dossier no.	5a332c1b-1d1b-4998-8115-d0929877ecb4
Segment usage	Refrigeration MT

PRODUCT DETAILS

Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	263 mm
Suction connection material	-
Suction connection pipe size [in]	5/8 in
Suction connection size [in]	1 1/4 in
Swept volume [cm ³]	60.47 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	356 mm
Type	MT036
UK RoHS compliance	Out of scope
Viscosity [cP]	32 cP
Voltage of capacitor A [V]	440 V
Voltage of capacitor B [V]	330 V
Voltage of capacitor C [V]	440 V